

Multi-Purpose/Wood Epoxy Systems

SP106 Multi Purpose Epoxy System (mix ratio 5:1 by volume) SP106 is a simple to use, all purpose epoxy which can be used unmodified as a protective primer, coating or laminating system. When modified with filler powders it can be used as an adhesive or filler system. Its various hardeners provide a range of working times. SP106 has been established for over 20 years as the primary epoxy system for the manufacture and repair of wooden boats and is now widely used in many other woodworking applications.

	Pack Size
SP 106	
0.85 kg resin & 0.15 kg hardener	1 kg
2.56 kg resin & 0.46 kg hardener	3.02 kg
10 kg resin & 1.8 kg hardener	11.8 kg
20 kg resin & 3.6 kg hardener (fast)	23.6kg

Handipack Multi-Purpose Epoxy System (mix ratio 2:1 by volume) Handipack is multi-purpose epoxy, supplied in a small pack designed for quick repair work and other small tasks. It is a simple 2:1 mix ratio and dispensing is made easy because pumps are supplied in the pack. Used as a coating it cures rapidly to form a tough, clear film, with good moisture resistance.

SP Handipack	375ml
---------------------	-------

Coatings

SP 320 Solvent Free Clear Epoxy Coating System (mix ratio 5:2 by volume) SP 320 is a solvent free, clear epoxy coating that provides high clarity tough finish to whatever it is applied to. When used for coating wood just a few coats will provide a depth of clarity that can only otherwise be achieved with many more coats of a conventional varnish. The epoxy coating will protect most surfaces from moisture ingress, and will also add strength to soft wood surfaces.

SP 320	0.75kg resin & 0.25kg hardener	1 kg
	3 kg resin & 1 kg hardener	4 kg
	10 kg resin & 3.33kg hardener	13.33 kg
	20 kg resin & 6.66kg hardener	26.66kg

Eposeal 300 Universal Epoxy Primer (mix ratio 1:1 by volume) Eposeal 300 is a solvent based, low viscosity epoxy primer. It has been developed primarily for use on wood but can also be used on other materials such as GRP, stone, ferrocement, brick etc. It's low viscosity ensures the product achieves rapid and deep penetration of porous surfaces.

Eposeal 300	0.5lt resin/0.5lt hardener	1 Lt
	2.5lt resin/2.5lt hardener	5Lt

Adhesives

Spabond 5 Min Adhesive - rapid bonding speed (bonds in 5 mins, full handling strength in 15/20 mins) Simple 1:1 by weight & volume

310ml Resin Cartridge & 310 ml
Hardener Cartridge